

O環尺寸表 (依內徑排序)

O-Ring Size List (Inner Diameter List)



材質	JIS 記號	1 種 A	1 種 B	3 種	4 種 C	4 種 D
	CNL 記號	NB7000K	NB9000K	EP7000K	SI7000R	VT7500K

單位 unit: mm

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09363-3.5	363	370	3.5	
*	09363-4	363	371	4	
*	09364-4	364	372	4	
*	09364.3-3.1	364.3	370.5	3.1	Gs-365
*	02365	364.3	375.7	5.7	G-365
*	01365	364.5	381.3	8.4	P-365
*	09365-2.5	365	370	2.5	
*	09365-3	365	371	3	
*	09365-4	365	373	4	
*	09365-5	365	375	5	
*	09365-5.3	365	375.6	5.3	
*	09365-6	365	377	6	
*	09366.5-6	366.5	378.5	6	V-370
*	09367-3.5	367	374	3.5	
*	09367.56-3	367.56	373.56	3	
	08458	367.67	381.65	6.99	AS-458
*	09368-5.33	368	378.66	5.33	
*	09369.6-3.1	369.3	375.5	3.1	Gs-370
*	02370	369.3	380.7	5.7	G-370
*	01370	369.5	386.3	8.4	P-370
*	09370-3	370	376	3	
*	09370-4	370	378	4	
*	09370-5	370	380	5	
*	09370-6	370	382	6	
*	09370-8	370	386	8	
*	09371.5-6	371.5	383.5	6	V-375
*	09372-3.5	372	379	3.5	
*	09374.3-3.1	374.3	380.5	3.1	Gs-375
*	02375	374.3	385.7	5.7	G-375
	01375	374.5	391.3	8.4	P-375
*	09375-2.5	375	380	2.5	
*	09375-3	375	381	3	
*	09375-4	375	383	4	
*	09375-5	375	385	5	
*	09375-6	375	387	6	
*	09375-7	375	389	7	
*	09375-8	375	391	8	
*	09375.79-1.8	375.79	379.39	1.8	
	09376-6	376	388	6	V-380
*	09378-1	378	380	1	


	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09379-1	379	381	1	
*	09379.3-3.1	379.3	385.5	3.1	Gs-380
*	02380	379.3	390.7	5.7	G-380
*	01380	379.5	396.3	8.4	P-380
*	09380-3	380	386	3	
*	09380-4	380	388	4	
*	09380-5	380	390	5	
*	09380-6	380	392	6	
*	09380-10	380	400	10	
	08384	380.37	391.03	5.33	AS-384
	08459	380.37	394.35	6.99	AS-459
	08281	380.6	387.66	3.53	AS-281
*	09381-6	381	393	6	V-385
*	09382-5	382	392	5	
*	09382-8	382	398	8	
*	09384.3-3.1	384.3	390.5	3.1	Gs-385
*	02385	384.3	395.7	5.7	G-385
	01385	384.5	401.3	8.4	P-385
*	09385-2.5	385	390	2.5	
*	09385-3	385	391	3	
*	09385-4	385	393	4	
*	09385-5	385	395	5	
*	09385-6	385	397	6	
*	09385-8	385	401	8	
*	09385-10	385	405	10	
*	09386-3.5	386	393	3.5	
*	09386-6	386	398	6	V-390
*	09388-6.99	388	401.98	6.99	
*	09389-7	389	403	7	
*	09389.3-3.1	389.3	395.5	3.1	Gs-390
*	02390	389.3	400.7	5.7	G-390
*	01390	389.5	406.3	8.4	P-390
*	09390-3	390	396	3	
*	09390-4	390	398	4	
*	09390-5	390	400	5	
*	09390-5.33	390	400.66	5.33	
*	09390-6	390	402	6	
*	09390-7	390	404	7	
*	09390-8	390	406	8	
*	09390-10	390	410	10	

O 環尺寸

* 符號代表國際規範外， 加耐力公司的特別尺寸 (* means CNL special design outside the international standard specifications)

O環尺寸表 (依內徑排序)

O-Ring Size List (Inner Diameter List)



材質	JIS 記號	1 種 A	1 種 B	3 種	4 種 C	4 種 D
	CNL 記號	NB7000K	NB9000K	EP7000K	SI7000R	VT7500K

單位 unit: mm

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09391-6	391	403	6	V-395
*	09391.41-5.33	391.41	402.07	5.33	
	08460	393.07	407.05	6.99	AS-460
*	09394-3.5	394	401	3.5	
*	09394.3-3.1	394.3	400.5	3.1	Gs-395
*	02395	394.3	405.7	5.7	G-395
*	01395	394.5	411.3	8.4	P-395
*	09395-2.5	395	400	2.5	
*	09395-3	395	401	3	
*	09395-4	395	403	4	
*	09395-5	395	405	5	
*	09396-6	396	408	6	V-400
*	09398-20	398	438	20	
*	09399.3-3.1	399.3	405.5	3.1	Gs-400
*	02400	399.3	410.7	5.7	G-400
*	09399.5-3.53	399.5	406.56	3.53	
	01400	399.5	416.3	8.4	P-400
*	09400-3	400	406	3	
*	09400-4	400	408	4	
*	09400-5	400	410	5	
*	09400-6	400	412	6	
*	09400-7	400	414	7	
*	09400-8	400	416	8	
*	09400-10	400	420	10	
*	09401-6	401	413	6	V-405
*	09403-5	403	413	5	
*	09404.3-3.1	404.3	410.5	3.1	Gs-405
*	02405	404.3	415.7	5.7	G-405
*	01405	404.5	421.3	8.4	P-405
*	09405-3	405	411	3	
*	09405-4	405	413	4	
*	09405-5	405	415	5	
*	09405-6	405	417	6	
	08282	405.26	412.32	3.53	AS-282
	08385	405.26	415.92	5.33	AS-385
	08461	405.26	419.24	6.99	AS-461
*	09406-3	406	412	3	
*	09406-4	406	414	4	
*	09406-6	406	418	6	V-410
*	09408-3	408	414	3	

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09409.3-3.1	409.3	415.5	3.1	Gs-410
*	02410	409.3	420.7	5.7	G-410
*	01410	409.5	426.3	8.4	P-410
*	09410-3	410	416	3	
*	09410-4	410	418	4	
*	09410-5	410	420	5	
*	09410-6	410	422	6	
*	09410-8	410	426	8	
*	09411-6	411	423	6	V-415
*	09412-7	412	426	7	
*	09414.3-3.1	414.3	420.5	3.1	Gs-415
*	02415	414.3	425.7	5.7	G-415
*	01415	414.5	431.3	8.4	P-415
*	09415-3	415	421	3	
*	09415-5	415	425	5	
*	09415-6	415	427	6	
*	09415-7	415	429	7	
*	09415.5-3	415.5	421.5	3	
*	09416-5	416	426	5	
*	09416-6	416	428	6	V-420
	08462	417.96	431.94	6.99	AS-462
*	09419.3-3.1	419.3	425.5	3.1	Gs-420
*	02420	419.3	430.7	5.7	G-420
*	01420	419.5	436.3	8.4	P-420
*	09420-3	420	426	3	
*	09420-4	420	428	4	
*	09420-5	420	430	5	
*	09420-5.33	420	430.66	5.33	
*	09420-6	420	432	6	
*	09420-10	420	440	10	
*	09420-11	420	442	11	
*	09421-6	421	433	6	V-425
*	09422-4	422	430	4	
*	09424.3-3.1	424.3	430.5	3.1	Gs-425
*	02425	424.3	435.7	5.7	G-425
*	01425	424.5	441.3	8.4	P-425
*	09425-3	425	431	3	
*	09425-3.1	425	431.2	3.1	
*	09425-3.5	425	432	3.5	
*	09425-4	425	433	4	

* 符號代表國際規範外， 加耐力公司的特別尺寸 (* means CNL special design outside the international standard specifications)

O環尺寸表 (依內徑排序)

O-Ring Size List (Inner Diameter List)



材質	JIS 記號	1 種 A	1 種 B	3 種	4 種 C	4 種 D
	CNL 記號	NB7000K	NB9000K	EP7000K	SI7000R	VT7500K

單位 unit: mm

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09425-5	425	435	5	
*	09425-7	425	439	7	
*	09425-8	425	441	8	
	09425.5-6	425.5	437.5	6	V-430
*	09426-6	426	438	6	
*	09427-3.5	427	434	3.5	
*	09427-5	427	437	5	
*	09428-6	428	440	6	
*	09428.1-8	428.1	444.1	8	
*	09429-5	429	439	5	
*	09429-6	429	441	6	
*	09429.3-3.1	429.3	435.5	3.1	Gs-430
*	02430	429.3	440.7	5.7	G-430
*	01430	429.5	446.3	8.4	P-430
*	09430-3	430	436	3	
*	09430-4	430	438	4	
*	09430-5	430	440	5	
*	09430-6	430	442	6	
*	09430-6.5	430	443	6.5	
*	09430-8	430	446	8	
*	09430-10	430	450	10	
*	09430.5-6	430.5	442.5	6	V-435
	08386	430.65	441.31	5.33	AS-386
	08283	430.66	437.72	3.53	AS-283
	08463	430.66	444.64	6.99	AS-463
*	09431-6	431	443	6	
*	09431.5-6	431.5	443.5	6	
*	09433.7-3	433.7	439.7	3	
*	09434-5	434	444	5	
*	09434.3-3.1	434.3	440.5	3.1	Gs-435
*	02435	434.3	445.7	5.7	G-435
*	01435	434.5	451.3	8.4	P-435
*	09435-3	435	441	3	
*	09435-4	435	443	4	
*	09435-5	435	445	5	
*	09435-6	435	447	6	
*	09435-8	435	451	8	
*	09435-10	435	455	10	
*	09435.5-6	435.5	447.5	6	V-440
*	09436-6	436	448	6	

	加耐力編號 CNL Part No.	內徑 d	外徑 D	線經 W	規格代碼
*	09438-4	438	446	4	
*	09439-6	439	451	6	
*	09439.3-3.1	439.3	445.5	3.1	Gs-440
*	02440	439.3	450.7	5.7	G-440
*	01440	439.5	456.3	8.4	P-440
*	09440-2.5	440	445	2.5	
*	09440-3	440	446	3	
*	09440-4	440	448	4	
*	09440-5	440	450	5	
*	09440-6	440	452	6	
*	09440-7	440	454	7	
*	09440-8	440	456	8	
*	09440-15	440	470	15	
*	09440.5-6	440.5	452.5	6	V-445
*	09441.71-3.53	441.71	448.77	3.53	
	08464	443.36	457.34	6.99	AS-464
*	09444-8	444	460	8	
*	09444.3-3.1	444.3	450.5	3.1	Gs-445
*	02445	444.3	455.7	5.7	G-445
*	01445	444.5	461.3	8.4	P-445
*	09445-3	445	451	3	
*	09445-3.53	445	452.06	3.53	
*	09445-5	445	455	5	
*	09445-5.33	445	455.66	5.33	
*	09445-8	445	461	8	
*	09445.5-6	445.5	457.5	6	V-450
*	09446-2.5	446	451	2.5	
*	09446-3.5	446	453	3.5	
*	09446-6	446	458	6	
*	09448-6	448	460	6	
*	09449.3-3.1	449.3	455.5	3.1	Gs-450
*	02450	449.3	460.7	5.7	G-450
*	01450	449.5	466.3	8.4	P-450
*	09450-3	450	456	3	
*	09450-4	450	458	4	
*	09450-5	450	460	5	
*	09450-7	450	464	7	
*	09450-10	450	470	10	
*	09450.1-5.7	450.1	461.5	5.7	
*	09450.5-6	450.5	462.5	6	V-455

O 環尺寸

* 符號代表國際規範外， 加耐力公司的特別尺寸 (* means CNL special design outside the international standard specifications)